

Model		VHC-150M	VHC-200M	VHC-250M	VHC-300M	VHC-500M	VHC-600M	
Treatment capacity (in the case of Mango)		1,500Kg/batch	2,000Kg/batch	2,500Kg/batch	3,000Kg/batch	5,000Kg/batch	6,000Kg/batch	
Size of chamber (LxWxH/mm)		3,920x2,440x3,160	5,120x2,440x3,160	6,320x2,440x3,160	7,520x2,440x3,160	12,320x2,440x3,160	13,520x2,440x3,160	
Operation pallet		3 palletes	4 palletes	5 palletes	6 palletes	10 palletes	12 palletes	
Performance	Temperature range	Room temperatures + 10°C to 60°C						
	Humidity range	50% to 98%RH						
	Temperature adjustment range	0.1°C						
	Humidity adjustment range	0.1%RH						
	Temperature distribution	±0.1°C						
	Humidity distribution	±1.0%						
Rating	Power source	Three-phase AC200V 50/60Hz						
	Maximum power consumption	75KW	95KW	115KW	140KW	230KW	270KW	
	Maximum water	During vapor heat treatment	18 liter/hr.	21 liter/hr.	24 liter/hr.	27 liter/hr.	48 liter/hr.	52 liter/hr.
	Consumption	During cooling	180 liter/min.	210 liter/min.	300 liter/min.	360 liter/min.	600 liter/min.	720 liter/min.